

Adjustable Scent Diffusing System

AirQ210

The Air-Q 210 system uses Prolitec's patented technology to diffuse fragrance and odor treatment products into the air.

Technical Characteristics

Reference : Air-Q 210
Type : 1 head nebulizer (cartridge sold separately)
Diameter of particles : Typically less than 1 μm

Power Input

Input : 100-240 VAC / 0.6 A
Frequency : 50 / 60 Hz
Protection : Switching power supply
Internal Power : 15 VDC / 1.0 A
Backup Battery : Lithium 3V, #CR2032

Dimensions

Height x Width x Depth : 219mm x 222mm x 98mm
Total weight : 2.2 kg

Wall Mounting Mechanism

Nylon mounting plate & screws included.
Ceiling track mounting optional.

Performance

Up to 425 m³ served.
With 1 air change per hour, cartridge will last up to 8 weeks, depending on usage.
Programmable start & stop times, adjustable output and 50 settings
Top or front output location.

Liquid Cartridges

One 175ml or 250ml cartridge containing fragrance and odor treatment products

Enclosure

Nylon plastic enclosure with lockable door

Approvals

FCC part 15
CE & ROHS compliant

Environment

0°C to 40°C operating temperature
85% or less operating relative humidity



Made in USA